

S-DIAS Digital Input Module

DI 080



with 8 inputs, input delay 5 ms

The S-DIAS DI 080 digital input module is equipped with eight inputs and a +24 V signal for reading the signal states "0" and "1". Input filters are available to suppress noise signals occurring in the signal lines.

Environmental Conditions

Storage temperature	-20 ... +85 °C	
Environmental temperature	0 ... +60 °C	
Humidity	0-95 %, non-condensing	
Operating conditions	pollution degree 2 altitude up to 2000 m	
EMC resistance	in accordance with EN 61000-6-2 (industrial area)	
EMC noise generation	in accordance with EN 61000-6-4 (industrial area)	
Vibration resistance	EN 60068-2-6	3.5 mm from 5-8.4 Hz 1 g from 8.4-150 Hz
Shock resistance	EN 60068-2-27	15 g
Protection type	EN 60529	IP20

Digital Input Specifications

Number	8	
Input voltage	typically +24 V	maximum +30 V
Signal level	low: < +5 V	high: > +15 V
Input current	3.7 mA at +24 V	
Input delay	typically 5 ms	

Electrical Requirements

Voltage supply from S-DIAS bus	+5 V	
Current consumption on the S-DIAS bus (+5 V supply)	typically 35 mA	maximum 40 mA

Article Number and Miscellaneous

Article number	20-006-080	
Dimensions	12.5 x 104.2 x 72 mm (W x H x D)	
Standard	UL 508 (E247993)	
Approvals	UL, cUL, CE	