

S-DIAS Digital Input Module DI 200



with 20 digital inputs, input delay 5 ms

The S-DIAS DI 200 digital input module has 20 inputs with a +24 V signal for reading the signal statuses „0“ and „1“. To suppress noise in the signal lines, input filters are provided.

Environmental Conditions

Storage temperature	-20 ... +85 °C	
Environmental temperature	0 ... +55 °C	
Humidity	0-95 %, non-condensing	
Operating conditions	pollution degree 2 altitude up to 2000 m	
EMC resistance	in accordance with EN 61000-6-2 (industrial area)	
EMC noise generation	in accordance with EN 61000-6-4 (industrial area)	
Vibration resistance	EN 60068-2-6	3,5 mm from 5-8,4 Hz 1 g from 8,4-150 Hz
Shock resistance	EN 60068-2-27	15 g
Protection type	EN 60529	IP20

Digital Input Specifications

Number	20	
Input voltage	typically +24 V	maximum +30 V
Signal level	low: < +5 V	high: > +15 V
Input current	3.7 mA at +24 V	
Input delay	typically 5 ms	

Electrical Requirements

Voltage supply from S-DIAS bus	+5 V	
Current consumption on the S-DIAS bus (+5 V supply)	typically 51 mA	maximum 56 mA

Article Number and Miscellaneous

Artikel number	20-006-200	
Dimensions	12.5 x 104.2 x 72 mm (W x H x D)	
Standard	UL 508 (E247993)	
Approvals	UL, cUL, CE	