

Build-in Touch Terminal ETT 1034



The ETT 1034 is an intelligent panel for visualizing, operating and monitoring automated processes.

A capacitive touch screen serves as the input medium for process data and parameters. The output is shown on a 10.1" TFT color display.

The available interfaces can be used to exchange process data or configure the multi-touch terminal. A microSD card serves as the storage medium for the operating system, application and application data.

Performance Data

Processor	EDGE2-Technology
Processor cores	2
Internal cache	32 kByte L1 Instruction Cache 32 kByte L1 Data Cache 512 kByte L2 Cache
Internal program and data memory (RAM)	1-Gbyte DDR3
Internal remnant data memory	512 kByte SRAM (battery buffered)
Internal storage device	1-Gbyte microSD
Internal I/O	no
Interfaces	1x USB-Host 2.0, Typ A (1x back) 1x Online-USB (Device), Typ Mini-B 2x Ethernet
Internal interfaces	1x IPS color display 1x USB (touch connection) 1x Panel Interface Connector

Display Resolution	10.1" TFT color display WXGA 1280 x 800 pixels	
Operating panel	Touch screen (projective capacitive)	
Signal generator	no	
Status LEDs	2 (red & green)	
Real-time clock	yes	
Cooling	passiv (fanless)	

Electrical Requirements

Supply voltage	typically +24 V DC	
	minimum +18 V DC	maximum +30 V DC
Current consumption of (+24 V) power supply	typically 600 mA (without external devices connected)	maximum 750 mA (with external devices connected)
Inrush current with 24 V/10 A fixed voltage supply	maximum 1.5 A (für 15 ms, load-dependent)	
Inrush current without current limiting supply	maximum 65 A (für 25 µs, load-dependent)	

Terminal

Dimensions	264 x 183 x 48 mm (W x H x D)
Material	front plate: 1.1 mm glass (touch screen) in black anodized aluminum frame housing; sheet steel
Weight	ca. 1.5 kg

Environmental Conditions

Storage temperature	-10 ... +70 °C	
Environmental temperature	0 ... +50 °C	
Humidity	10-95 %, non-condensing	
Installation altitude above sea level	0-2000 m without derating, > 2000 m with derating of the maximum environment temperature by 0.5 °C per 100 m	
Operating conditions	pollution degree 2	
EMC resistance	according to EN 61000-6-2:2007 (industrial area)	
EMC noise generation	according to EN 61000-6-4 (industrial area)	
Vibration resistance	EN 60068-2-6	2-9 Hz: amplitude 3.5 mm 9-200 Hz: 1 g (9.81 m/s ²)
Shock resistance	EN 60068-2-27	15 g (147.15 m/s ²) duration 11 ms, 18 shocks
Protection type	EN 60529 protected through the housing	front: IP65 cover: IP20

10.1" WXGA Display

Type	10.1" IPS color display
Resolution	WXGA 1280 x 800 pixles
Color depth	18-bit RGB
LCD mode	normally black
LCD Polarizer	transmissive
Pixel size	0.1695 x 0.1695 mm
Active surface	216.96 x 135.60 mm
Backlighting	LED
Contrast	typically 1000
Brightness	typically 500 cd/m²
Blickwinkel	left, right, top, bottom typically 85°

Article Number and Miscellaneous

Article number	01-230-1034
Operating system	Salamander
Approvals	CE ETT 1034 consists of TP 1061 und PIM 031, both UL certified „UL _{us} (E247993)

Notes

