

Built-In Terminal ET 1520



with 15.6" TFT color display

The ET 1520 is an intelligent panel for visualizing, operating and monitoring automated processes. Process diagnostics is therewith simplified. A projective capacitive touch screen serves as the input medium for process data and parameters. The output is shown on a 15.6" TFT color display. With the LASAL visualization tool, graphics can be created on the PC, then stored and displayed on the handheld operating panel. Additionally, an integrated UPS ensures continued operation during short-term power interruptions.

Performance Data

Processor	Intel® Celeron J6412
Processor cores	4
Processor clock	4x 2 GHz (2.6 GHz Burst Mode)
Internal program and data memory (RAM)	4-Gbyte (DDR4)
Internal remnant data memory	512-kByte
Internal storage device	128-Gbyte M.2 SSD (1:1 formatted ~3k P/E cycles)
Optional memory expansion	no
Graphic	Intel® UHD Graphic Gen10
Interfaces	2x Ethernet (10/100/1000) 4x USB 3.0 Host Type A
Internal interface connections and devices	1x internal UPS (approx. 2 s buffer time)
Operating components	no
Signal generator	no
Display Resolution	15.6" TFT color display FullHD 1920 x 1080 pixels
Operating field	Touch screen (multi-touch, projective capacitive)

Status LEDs	yes (1x red)
Real-time clock	yes (battery buffered)
Cooling	passive

Electrical Requirements

Supply voltage	+24 V DC ±20 % (SELV/PELV) UL: NEC Class 2	
Protection class	III	
Current consumption of power supply (+24 V)	typically 0.8 A (with no external devices connected)	maximum 1.36 A (with external devices connected)
Inrush current without currentlimiting supply	6.68 A for 133 us	
Inrush current with 24 V/10 A fixed voltage supply	2.14 A for 7 s	

Terminal

Dimensions	394.2 x 245.6 x 60.8 mm (W x H x D)
Material	Housing: natural aluminum Color: black Front: glass black 1.8 mm
Weight	2.9 kg

Display

Type	15.6" TFT color display
Resolution	FullHD 1920 x 1080 pixels
Color depth	24-Bit RGB
LCD mode	normally black
LCD Polarizer	transmissive
Pixel size	0.17925 x 0.17925 mm
Active range	344.16 x 193.59 mm
Backlighting	LED
Contrast ratio	typically 1000:1
Brightness	typically 250 cd/m²
Angle CR ≥ 10	left, right, up, bottom typically 89°
Life span	By compliance with the ambient conditions, the brightness of the display sinks after 30.000 operating hours to 50 % of the original brightness.

Control Unit

Operating field	Touch screen (multi-touch, projective capacitive)
Maximum number of fingers	10
The operation with thin gloves	yes
SIGMATEK Touch pen (passive)	yes
Handwriting recognition	no
Ball of the thumb recognition	yes
Water spray recognition ¹⁾	yes
Water detection ²⁾	no

Input

Input	Multi-touch screen (PCAP)
-------	---------------------------

Environmental Conditions

Storage temperature	-10 ... +70 °C	
Environmental temperature	0 ... +50 °C	
Humidity	10-95 %, non-condensing	
Installation altitude above sea level	0-2000 m without derating > 2000 m up to a maximum of 5000 m with derating of the maximum environmental temperature by 0.5 °C per 100 m	
Operating conditions	pollution degree 2	
Noise emissions	≤ 70 dB	
EMC resistance	EN 61000-6-2 (industrial area)	
EMC noise generation	EN 61000-6-4 (industrial area)	
Vibration resistance	EN 60068-2-6	3.5 mm from 5-8.4 Hz 1 g from 8.4-150 Hz
Shock resistance	EN 60068-2-27	15 g (147.15 m/s²)
Protection type	EN 60529	Front: IP65 Rear: IP20 (without interface cover) IP54 (with interface cover)

Article Number and Miscellaneous

Article number	01-235-1520	
Operating system	Salamander	
Default IP address	10.10.150.1	
Printed circuit board coating	no	
Approvals	CE	yes
	UL	designed according to UL
	Functional Safety	no
	UKCA	no

Notes