

Touch Operating Panel ETT 1064



with 10.1" TFT color display

The ETT 1064 is an intelligent panel for visualizing, operating and monitoring automated processes. Process diagnostics is therewith simplified.

A projective capacitive touch screen serves as the input medium for process data and parameters. The output is shown on a 10.1" TFT color display.

The available interfaces can be used to exchange process data or configure the multitouch terminal.

Performance Data

Processor	EDGE3 Technology
Processor cores	4
Internal program and data memory (RAM)	2-Gbyte (DDR4)
Internal remnant data memory	128-kByte FRAM
Internal storage device	8-Gbyte microSD
Optional memory expansion	no
Graphic	integrated in EDGE processor
Interfaces	2x Ethernet (10/100/1000) 2x USB 2.0 Type A 1x USB 2.0 Type Mini-B OTG 1x microSD card holder (SD 3.0)
Internal interface connections and devices	no
Operating components	no

Signal generator	no
Display Resolution	10.1" TFT color display WXGA 1280 x 800 pixels
Operating field	Touch screen (multi-touch, projective capacitive)
Status LEDs	yes (1x red/1x green)
Real-time clock	yes (battery buffered)
Cooling	passive

Electrical Requirements

Supply voltage	+24 V DC $\pm 20\%$ (SELV/PELV) UL: Class 2 of LVLC	
Protection class	III	
Current consumption of power supply at +24 V	typically 450 mA (with no external devices connected)	maximum 580 mA (with external devices connected)
Inrush current without currentlimiting supply	30 A for max. 20 μ s	
Inrush current with 24 V/10 A fixed voltage supply	1 A for max. 30 ms	

Terminal

Dimensions	264 x 183 x 38 mm (W x H x D)
Material	Housing: aluminium/steel chromated Color: black Front: glass 1.1 mm
Weight	1.24 kg

Environmental Conditions

Storage temperature	-10 ... +70 °C	
Environmental temperature	0 ... +55 °C	
Humidity	10-95 %, non-condensing	
Installation altitude above sea level	0-2000 m without derating > 2000 m up to a maximum of 5000 m with derating of the maximum environmental temperature by 0.5 °C per 100 m	
Operating conditions	pollution degree 2	
EMC resistance	EN 61000-6-2 (industrial area)	
EMC noise generation	EN 61000-6-4 (industrial area)	
Vibration resistance	EN 60068-2-6	3.5 mm from 5-8,4 Hz 1 g from 8.4-150 Hz
Shock resistance	EN 60068-2-27	15 g (147.15 m/s ²)
Protection type	EN 60529/NEMA 250 protection through housing	front: IP65/Type4 cover: IP20/Type1

Display		
	Type	10.1" TFT color display
	Resolution	WXGA 1280 x 800 pixels
	Color depth	18-Bit RGB
	LCD mode	normally black
	LCD polarizer	transmissive
	Pixel size	0.1695 x 0.1695 mm
	Active range	216.96 x 135.60 mm
	Backlighting	LED
	Contrast	typically 1000:1
	Brightness	typically 500 cd/m²
	Visible field	left, right, top, bottom typically 85°
	Life span	By compliance with the ambient conditions, the brightness of the display sinks after 50,000 operating hours to 50 % of the original brightness.

Article Number and Miscellaneous		
	Article number	01-230-1064
	Operating system	Gecko
	Standard	designed according to UL
	Approvals	CE

Notes